


T8 Triphosphor



A comprehensive range of 26mm diameter Triphosphor fluorescent tubes providing excellent colour rendering, high output and extended life.

- 15,000 hour life
- SPECTRA-PLUS Triphosphor
- 3000K warm white, 3500K white, 4000K cool white or 6400K daylight colour options
- Excellent colour rendering and high lumen maintenance

Product Code	Watts (W)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Colour Rendering Index/Group	Dimensions (mm)			Energy Rating	Order Qty
							Dia	L1	L2		
Single Sleeve											
FT1815SPW	15	G13	White	3500	960	85/1B	26	450	438	B	25
FT1815PCW	15	G13	Cool White	4000	960	85/1B	26	450	438	B	25
FT1815PDYLT	15	G13	Daylight	6400	900	85/1B	26	450	438	B	25
FT218SPWW	18	G13	Warm White	3000	1350	85/1B	26	604	590	A	25
FT218SPW	18	G13	White	3500	1350	85/1B	26	604	590	A	25
FT218PCW	18	G13	Cool White	4000	1350	85/1B	26	604	590	A	25
FT218PDYLT	18	G13	Daylight	6400	1350	85/1B	26	604	590	A	25
FT330SPW	30	G13	White	3500	2400	85/1B	26	910	895	A	25
FT330PCW	30	G13	Cool White	4000	2400	85/1B	26	910	895	A	25
FT330PDYLT	30	G13	Daylight	6400	2200	85/1B	26	910	895	A	25
FT436SPWW	36	G13	Warm White	3000	3350	85/1B	26	1212	1200	A	25
FT436SPW	36	G13	White	3500	3350	85/1B	26	1212	1200	A	25
FT436PCW	36	G13	Cool White	4000	3350	85/1B	26	1212	1200	A	25
FT436PDYLT	36	G13	Daylight	6400	3350	85/1B	26	1212	1200	A	25
FT558SPWW	58	G13	Warm White	3000	5200	85/1B	26	1510	1500	A	25
FT558SPW	58	G13	White	3500	5200	85/1B	26	1510	1500	A	25
FT558PCW	58	G13	Cool White	4000	5200	85/1B	26	1510	1500	A	25
FT558PDYLT	58	G13	Daylight	6400	5200	85/1B	26	1510	1500	A	25
FT670SPW	70	G13	White	3500	6300	85/1B	26	1775	1763	A	25
FT670PCW	70	G13	Cool White	4000	6300	85/1B	26	1775	1763	A	25
FT670PDYLT	70	G13	Daylight	6400	5800	85/1B	26	1775	1763	A	25



G13 Cap



Experts in lighting since 1878

Shatterproof T8 Triphosphor




We now provide a range of fluorescent tube coatings for fragment retention. Our non-foodsafe coating is IEC 61549 compliant and are banded with a dual green band. These are an economical option for standard lamps for open and enclosed fittings.

- 15,000 hour life
- SPECTRA-PLUS Triphosphor
- 3000K warm white, 3500K white, 4000K cool white or 6400K daylight colour options
- Excellent colour rendering and high lumen maintenance

Product Code	Watts (W)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Colour Rendering Index/Group	Dimensions (mm)			Energy Rating	Order Qty
							Dia	L1	L2		
Single Sleeve											
FT1815SPW-S	15	G13	White	3500	960	85/1B	26	450	438	B	25
FT1815PCW-S	15	G13	Cool White	4000	960	85/1B	26	450	438	B	25
FT1815PDYLT-S	15	G13	Daylight	6400	900	85/1B	26	450	438	B	25
FT218SPWW-S	18	G13	Warm White	3000	1350	85/1B	26	604	590	A	25
FT218SPW-S	18	G13	White	3500	1350	85/1B	26	604	590	A	25
FT218PCW-S	18	G13	Cool White	4000	1350	85/1B	26	604	590	A	25
FT218PDYLT-S	18	G13	Daylight	6400	1350	85/1B	26	604	590	A	25
FT330SPW-S	30	G13	White	3500	2400	85/1B	26	910	895	A	25
FT330PCW-S	30	G13	Cool White	4000	2400	85/1B	26	910	895	A	25
FT330PDYLT-S	30	G13	Daylight	6400	2200	85/1B	26	910	895	A	25
FT436SPWW-S	36	G13	Warm White	3000	3350	85/1B	26	1212	1200	A	25
FT436SPW-S	36	G13	White	3500	3350	85/1B	26	1212	1200	A	25
FT436PCW-S	36	G13	Cool White	4000	3350	85/1B	26	1212	1200	A	25
FT436PDYLT-S	36	G13	Daylight	6400	3350	85/1B	26	1212	1200	A	25
FT558SPWW-S	58	G13	Warm White	3000	5200	85/1B	26	1510	1500	A	25
FT558SPW-S	58	G13	White	3500	5200	85/1B	26	1510	1500	A	25
FT558PCW-S	58	G13	Cool White	4000	5200	85/1B	26	1510	1500	A	25
FT558PDYLT-S	58	G13	Daylight	6400	5200	85/1B	26	1510	1500	A	25
FT670SPW-S	70	G13	White	3500	6300	85/1B	26	1775	1763	A	25
FT670PCW-S	70	G13	Cool White	4000	6300	85/1B	26	1775	1763	A	25
FT670PDYLT-S	70	G13	Daylight	6400	5800	85/1B	26	1775	1763	A	25

Crompton Lamps shatterproof fluorescent tubes are coated in a special material with the sole purpose of fragment retention. A fluorescent tube breakage can put a costly stop to production, as well as obvious health risks that glass fragments can create. A common misconception is that the glass tube itself is shatterproof, when in fact it is the sleeve acting as an aid to glass retention. The material is either extruded or heat shrunk to a fluorescent lamp, acting as a glass collector should the lamp itself shatter.



G13 Cap



Experts in lighting since 1878

Foodsafe Shatterproof T8 Triphosphor




We now provide a range of fluorescent tube coatings for fragment retention. Our foodsafe coating, which is IEC 61549 compliant and also used for long life lamps is recognisable by a green band.

- 15,000 hour life
- SPECTRA-PLUS Triphosphor
- 3000K warm white, 3500K white, 4000K cool white or 6400K daylight colour options
- Excellent colour rendering and high lumen maintenance

Product Code	Watts (W)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Colour Rendering Index/Group	Dimensions (mm)			Energy Rating	Order Qty
							Dia	L1	L2		
Single Sleeve											
FT1815SPW-SF	15	G13	White	3500	960	85/1B	26	450	438	B	25
FT1815PCW-SF	15	G13	Cool White	4000	960	85/1B	26	450	438	B	25
FT1815SPDYLT-SF	15	G13	Daylight	6400	900	85/1B	26	450	438	B	25
FT218SPWW-SF	18	G13	Warm White	3000	1350	85/1B	26	604	590	A	25
FT218SPW-SF	18	G13	White	3500	1350	85/1B	26	604	590	A	25
FT218PCW-SF	18	G13	Cool White	4000	1350	85/1B	26	604	590	A	25
FT218PDYLT-SF	18	G13	Daylight	6400	1350	85/1B	26	604	590	A	25
FT330SPW-SF	30	G13	White	3500	2400	85/1B	26	910	895	A	25
FT330PCW-SF	30	G13	Cool White	4000	2400	85/1B	26	910	895	A	25
FT330SPDYLT-SF	30	G13	Daylight	6400	2200	85/1B	26	910	895	A	25
FT436SPWW-SF	36	G13	Warm White	3000	3350	85/1B	26	1212	1200	A	25
FT436SPW-SF	36	G13	White	3500	3350	85/1B	26	1212	1200	A	25
FT436PCW-SF	36	G13	Cool White	4000	3350	85/1B	26	1212	1200	A	25
FT436PDYLT-SF	36	G13	Daylight	6400	3350	85/1B	26	1212	1200	A	25
FT558SPWW-SF	58	G13	Warm White	3000	5200	85/1B	26	1510	1500	A	25
FT558SPW-SF	58	G13	White	3500	5200	85/1B	26	1510	1500	A	25
FT558PCW-SF	58	G13	Cool White	4000	5200	85/1B	26	1510	1500	A	25
FT558PDYLT-SF	58	G13	Daylight	6400	5200	85/1B	26	1510	1500	A	25
FT670SPW-SF	70	G13	White	3500	6300	85/1B	26	1775	1763	A	25
FT670PCW-SF	70	G13	Cool White	4000	6300	85/1B	26	1775	1763	A	25
FT670SPDYLT-SF	70	G13	Daylight	6400	5800	85/1B	26	1775	1763	A	25

Crompton Lamps shatterproof fluorescent tubes are coated in a special material with the sole purpose of fragment retention. A fluorescent tube breakage can put a costly stop to production, as well as obvious health risks that glass fragments can create. A common misconception is that the glass tube itself is shatterproof, when in fact it is the sleeve acting as an aid to glass retention. The material is either extruded or heat shrunk to a fluorescent lamp, acting as a glass collector should the lamp itself shatter.



G13 Cap



Experts in lighting since 1878