

# LED CFL Single Turn L Type 4 Pin



LED glass energy efficient lamps often used for office lighting and in public buildings, these lamps are designed to replace CFL PLL equivalents and use less than half the wattage.

- 30,000 hour life
- 15,000 switching cycles
- 2 year warranty
- 3000K warm white and 4000K cool white colour options
- Colour rendering index Ra≥80
- 2G11 4-Pin cap
- Full glass body
- 270° Beam angle
- Pearl finish
- Passive heatsink design
- Not suitable for dimming
- Recommended for indoor use only

Product Code	Watts (W)	Volts (V)	Cap	Colour Appearance	Colour Temp (K)	Total Lumens (lm)	Dimensions (mm)		Energy Rating	Order Qty
							Dia	H		
<b>18W Equivalent - Single Carton</b>										
LL18WW	8	220-240	2G11	Warm White	3000	800	44	230		10
LL18CW	8	220-240	2G11	Cool White	4000	840	44	230		10
<b>24W Equivalent - Single Carton</b>										
LL24WW	12	220-240	2G11	Warm White	3000	1200	44	320		10
LL24CW	12	220-240	2G11	Cool White	4000	1260	44	320		10
<b>36W Equivalent - Single Carton</b>										
LL36WW	18	220-240	2G11	Warm White	3000	1980	44	410		10
LL36CW	18	220-240	2G11	Cool White	4000	2070	44	410		10
<b>40W Equivalent - Single Carton</b>										
LL40WW	20	220-240	2G11	Warm White	3000	2200	44	530		10
LL40CW	20	220-240	2G11	Cool White	4000	2310	44	530		10
<b>55W Equivalent - Single Carton</b>										
LL55WW	24	220-240	2G11	Warm White	3000	2750	44	530		10
LL55CW	24	220-240	2G11	Cool White	4000	2875	44	530		10

DIRECT-TO-MAINS: Requires Ballast bypass, wire direct-to-mains only.



2G11 4-Pin Cap



Lighting brilliance since 1878



Crompton Lamps Limited registered in England and Wales No. 05590551  
 Registered office and correspondence address: Unit 2, Martree Business Park, Bowling Back Lane, Bradford BD4 8QE  
**Tel:** +44 (0)1274 657 088 **Fax:** +44 (0)1274 657 087 **Email:** sales@cromptonlamps.com **Web:** www.cromptonlamps.com

All images and specifications are for illustration purposes only and are subject to change without notice.  
 E. & O. E. © Crompton Lamps Limited 2024